

Hydr. pressbrake

Promecam RG-125



Sorry the machine has been sold already!

stock-no.:	0100241
type of machine:	Hydr. pressbrake
make:	Promecam
type:	RG-125
year of manufacture:	1971
type of control:	other
country of origin:	France
storage location:	Leipzig 2
delivery time:	5 days
freight basis:	EXW, free on truck unpacked
price:	on request



technical details

pressure:	125 t
chamfer length:	1250 mm
distance between columns:	mm
throat:	400 mm
distance between columns:	1050 mm
stroke:	unterer Balken: 100 mm
throat min.:	an den Ständern: 400 mm
daylight between press beam:	max. 300 mm
adjustment speed:	39 mm/sec
working feed:	10 mm/sec
return speed:	50 mm/sec
back gauge:	380mm manuell
total power requirement:	13,5 (18 PS) kW
weight of the machine ca.:	4,7 t
machine dimensions LxWxH:	2,1 x 1,8 x 2,8 m
transport dimensions LxWxH:	1,7 x 1,8 x 2,8 m

additional information

This press brake allows free bending and air bending, as well as bending by embossing. Through special tools, hole punching can also be done.

Other technical features:

- passage with mounted tool intermediate beam = 300mm.
- the lower press beam has a stroke max. 100mm
- the upper pressing beam is fixed

Equipment:

- Hydraulics, with oil tank size for 80 liters, pump capacity 20l/min.

Accessories:

- 6x div prisms for bottom

Hydr. pressbrake Promecam RG-125



-15x div. dies wedge shapes for top
-5x div. forming punches for above

The machine must be placed in the foundation! (approx. 750mm)