

# Radial Drilling Machine

## WEBO BR 50/63-H 2000



|                      |                             |
|----------------------|-----------------------------|
| stock-no.:           | 0200331                     |
| type of machine:     | Radial Drilling Machine     |
| make:                | WEBO                        |
| type:                | BR 50/63-H 2000             |
| year of manufacture: | 1966                        |
| type of control:     | conventional                |
| country of origin:   | Germany                     |
| storage location:    | Leipzig 2                   |
| delivery time:       | immediately                 |
| freight basis:       | EXW, free on truck unpacked |
| price:               | on request                  |



### technical details

|                                    |   |
|------------------------------------|---|
| bore capacity in steel (diameter): | 63 mm   |
| arm length::                       | 2000  |
| workpiece height max.:             | 1270 mm                                       |
| spindle taper MT:                  | MK 5  |
| drill depth:                       | 400 (Hub) mm                                  |
| quill stroke:                      | 400 mm  |
| feed:                              | 0,05 - 0,32 m/min                             |
| revolutions per minute spindle::   | 14 - 1000 (40/50/63/160+200 o.Funktion) U/min |
| column turnable:                   | 360 °   |
| electrics - voltage/frequency:     | 380/50 V/Hz                                   |
| base plate:                        | 1900 x 950 mm                                 |
| total power requirement:           | 13 kW   |
| weight of the machine ca.:         | 7,9 t   |
| space requirements approx. LxWxH:  | 3,9 x 1,5 x 3,4 m                             |

### additional information

This radial drilling machine has an electric sliding table!

Further features:

- Distance from spindle center to stand: 360 - 2000mm
- Distance from drill chuck to table top: 1270mm
- Distance from spindle to base plate: 1220 - 4520mm
- Drilling capacity in St 60: 63mm at feed rate 0.32
- Drilling capacity in GG 22: 80mm at feed rate 0.5
- Horizontal travel of the drilling head: 1640mm
- Vertical travel of the drill head: 980mm
- Distance from spindle nose to base plate: 430-1770mm

Equipment:

- Coolant pump (out of function)
- Support stand
- 1 electrically driven sliding table 1250 x 1000mm type TI 18 with digital display (interface to the machine)
- incl. machine vice

Not all revolutions are currently selectable.  
i.D.