

# Lip trimmer

## Pullmax X93 76000-13



|                      |                             |
|----------------------|-----------------------------|
| stock-no.:           | 0800040                     |
| type of machine:     | Lip trimmer                 |
| make:                | Pullmax                     |
| type:                | X93 76000-13                |
| year of manufacture: | nicht bekannt               |
| type of control:     | conventional                |
| country of origin:   | Sweden                      |
| storage location:    | Leipzig 3                   |
| delivery time:       | on request                  |
| freight basis:       | EXW, free on truck unpacked |
| price:               | on request                  |



### technical details

|                          |                   |
|--------------------------|-------------------|
| x-travel:                | mm                |
| plate thickness:         | mm                |
| work piece width:        | mm                |
| voltage:                 | 380 V             |
| total power requirement: | 4,0 kW            |
| machine weight approx.:  | 1270 kg           |
| dimensions L x W x H:    | 1,4 x 1,0 x 1,9 m |

### additional information

#### EDGE CHAMFERING MILLING MACHINE

Application: Beveling of circular blanks and flat material

- smallest straight edge = 3mm
- max. breaking strength of the material = 70 kp/mm (690 N/mm<sup>2</sup>)
- max. feed rate:
  - at 10mm bevel width = 3,1 m/min.
  - at 15mm bevel width = 2,9 m/min.
  - at 20mm bevel width = 2,7 m/min.
  - at 25mm bevel width = 1,5 m/min.

with degree adjustment (bevel angle) 25° - 55°.

scale for setting the straight edge

downholder manual with handwheel

cutting wheel size Ø 200mm; teeth fine / medium / rough

Support block size: D:220 x W:620 x H:350mm; driving wheel approx. Ø 350 x 100mm; display via linear scale