Circular saw BEHRINGER-EISELE PSU 450 H



| stock-no.: | 1000425 |
|----------------------|-----------------------------|
| type of machine: | Circular saw |
| make: | BEHRINGER-EISELE |
| type: | PSU 450 H |
| year of manufacture: | 2007 |
| type of control: | conventional |
| country of origin: | Germany |
| storage location: | Leipzig 5 |
| delivery time: | immediately |
| freight basis: | EXW, free on truck unpacked |
| price: | on request |



technical details

| Saw blade diameter: | mm |
|-----------------------------------|--|
| cutting diameter: | mm |
| feed:: | m/min |
| saw blade diameter: | Ø 400 - 450 mm |
| hole of sawblade: | Ø 50 mm |
| revolution per minute: | Spindel: 6 / 12 / 24 / 48 (2 step) U/min |
| revolution per minute: | Motor: 1400 / 2800 U/min |
| cutting range 90 degrees: round: | Ø 150 mm |
| cutting range 90 degrees: square: | 140 x 140 mm |
| cutting range 90 degrees: flat: | 400x30 / 345x70 / 300x95 mm |
| table-size: | Ø 700 mm |
| table rotating: | 360 ° |
| air-pressure connection: | 6 - 8 bar |
| total power requirement: | 3,6 kW |
| weight of the machine approx .: | 1900 kg |
| dimensions of machine: | T:1,5 x B:1,0 x H:2,35 m |

additional information

CIRCULAR SAW SEMI-AUTOMATIC - PROFILE CIRCULAR SAW MACHINE - UNDERFLOOR SAW

Profile circular saw with two-hand control for sawing materials: steel as solid material, pipes and profiles, taking into account the cutting area. Cutting speed depends on the material to be sawn Mitre: 30° - 45° - 90° Operating pressure/clamping pressure: 50bar / 30bar adjustable Hydraulic pump 2.2 kW power output Coolant system with pump Operation via control panel / two-hand operation