

Shotblasting line

RÖSLER RRBK 31/16



Sorry the machine has been sold already!

| | |
|----------------------|-------------------|
| stock-no.: | 1200519 |
| type of machine: | Shotblasting line |
| make: | RÖSLER |
| type: | RRBK 31/16 |
| year of manufacture: | Aufbau 2012 |
| type of control: | conventional |
| country of origin: | Germany |
| storage location: | Plauen |
| delivery time: | on request |
| freight basis: | EXW |
| price: | on request |



technical details

| | |
|----------------------------|-------------------------|
| through-put width: | - mm |
| through-put width: | max. 3200 mm |
| working height: | min/max: 6/1600 mm |
| control: | SPS Simatic S 7-300 |
| workpiece length - min.: | 2500 mm |
| workpiece weight: | 2000 / lfd. Meter kg |
| Number of turbines: | 16 / 22 kW Stück / kW |
| Number of working hours: | Strahlanl.=1000 h |
| speed: | 0,8 - 10 m/min |
| cleansing medium: | Stahlguss Dm=0,9-1,2 mm |
| air consumption: | 6 bar |
| total power requirement: | Anfrage kW |
| weight of the machine ca.: | Anfrage t |

additional information

Throughput Shot blasting machine - fan blower System

consists of: Roles to and finish (hydraulic lifting / lowering of the rollers) for roller conveyor with frequency converter drives

- input roller conveyor path 21 meters

- output roller conveyor path 28 meters incl. set return transport augers (height above ground of both roller conveyors approx 1000mm)

Blasting Machine:

-Rösler Construction spotlights RRBK 34/16

- parallel separator

- workpiece cleaning system incl. automatic. height adjustment workpiece cleaning

- inspection platform with ladder

- blower wheel with chilled cast iron lining; Impeller diameter 420mm; Drive each impeller 22kW;

Filter system:

-Rösler Filter system RF 150 / 18-2 P / w

- pipe connection intermediate jet and filter system

- sound absorbing cover

-automatic blasting material re-dosing

Shotblasting line

RÖSLER RRBK 31/16



Electric cabinet with PLC control

For more information about the system, please contact us.