Pneumatic Press Parker EOMAT eco



Sorry the machine has been sold already!

stock-no .: 1201017

type of machine: Pneumatic Press

Parker make: EOMAT eco type:

year of 2008

manufacture:

type of control: conventional country of origin: Germany storage location: Leipzig 1 delivery time: on request freight basis: in calculation

price: on request



technical details

pressure:	t
distance between columns:	mm
stroke:	mm
cycle time:	sec
working pressure:	220 bar
Voltage:	230 V / 50Hz / - 700Watt V
machine weight approx.:	32 kg
dimensions of machine:	ca. L: 750 x B: 360 x H: 260 mm

additional information

HYDROPNEUMATIC HOSE PRESS / Hose Assembly Machine

Consists of hose assembly machine and aitrhydraulic pump.

Application Hose Assembly Machine:

Pressing hydraulic hoses with 1 and 2 steel braid and/or textile braid inserts.

The aitrhydraulic pump ENERPAC Turbo works by means of compressed air driven hydraulics. Operation by pedal. Tank capacity 2081 cm³; air pressure range 2.8 - 8.5 bar; air consumption 340 l/min; delivery volume max. 0.16 l/min.

Crimping of steel mesh up to size 20 Compressed air driven hydraulics Pedal for control

with 3-3 way valve

Compressed air from 2,1 - 8,6 bar with consumption from 283 - 991 l/min.

The hose assembling machine can be moved by the extendable handle.

We offer the following press jaws from the manufacturer Parker optionally for 100.00 Euro net per set, e.g.:

1x C04 1xP03

1x C05 1xP04

1x C06 1xP05

1xP08

WMW AG Tel: +49 (0341) - 52 04 60 Messeallee 10a Fax: +49 (0341) - 52 04 61 7 D-04158 Leipzig

Mail: info@wmwag.com Web: http://www.wmwag.com

Pneumatic Press Parker EOMAT eco



Mail: info@wmwag.com

Web: http://www.wmwag.com

We offer the following press jaws from the manufacturer Parker as an option for 150.00 euros net per set: 1x P12 1x C16 1x P16 1x C20

Tel: +49 (0341) - 52 04 60

Fax: +49 (0341) - 52 04 61 7