

Spot Welding Machine

NIMAK PMP6-2/100MF-A/SH60048.1



stock-no.:	1303000
type of machine:	Spot Welding Machine
make:	NIMAK
type:	PMP6-2/100MF-A/SH60048.1
year of manufacture:	-
type of control:	conventional
country of origin:	Germany
storage location:	Leipzig 1
delivery time:	on request
freight basis:	EXW, free on truck unpacked
price:	on request



technical details

current capacity:	100 kVA
throat:	600 mm
arm distance:	600 mm
control:	Bosch Programmier-Feldbusse
pincer opening adjustable:	240 - 540
interface:	RS 485
voltage:	500 V
connection voltage:	380 V
air pressure:	6 bar
cooling water consumption:	14 l/min
weight of the machine approx.:	770 kg
space requirements of the machine approx.:	1,5 x 0,95 x 2,1 m

additional information

SPOT WELDING MACHINE - WELDING TRANSFORMER

Application: Spot, projection and series spot welding

1 - 1000 Hz

Lifting cylinder electrode force 11 daN

PSI 6000 medium frequency inverter with integrated control function (50/60 Hz AC mains voltage)

Electrode arm Ø 35mm

Electrode holder adjustment 200mm (manual)

Arm distance min. 240mm max.: 540mm Manual adjustment

Operation via Rexroth IntraControl VCP05 control panel and foot switch

incl. replacement electrodes (water-cooled)